

DR. FIXIT GAP SEAL TAPE

Self Adhesive Bituminous Strip with Aluminums Foil Finish

Description:

DR. Fixit Gap Seal Tape is self-adhesive, aluminum or high density polyethylene surfaced bitumen & SBS rubber backed sealing strip. It is a quick, efficient and cost effective method of flashing, sealing and repair that produces a lasting protection in all climates.

Area of Application

- Replacement or repair of flashing
- Guttering, down pipes. Sky lights
- Extensions, porches. Window frames & chimneys
- Caravans & Conservatories
- Sealing parapets, Valley gutters
- Seals capping bolts & roof ridges
- Roof repair of portable buildings



Method of Application

1. Surface Preparation:

- The substrate must be clean and free of dust or other loose materials.

2. Application

- Make sure the surface smooth, clean, no dust or other loose material
- Cut the flash band to required length
- Remove the release paper. Press flash band into place, using fingertip pressure. Avoid excessive pressure
- When laying adjacent rolls the flash band must overlap by at least 25mm
- Use a steam roller or rounded piece of wood to smooth the flash band and ensure good contact is made
- **Overpainting :**
- Flash band can be overpainted with conventional decorative paints, though a little staining may occur at the edges.

DR. FIXIT GAP SEAL TAPE

Self Adhesive Bituminous Strip with Aluminums Foil Finish

Precautions & Limitations

- In cold weather, application will be made easier by warming the surface and by storing flashing band in a warm place prior to use. Do not apply if surface temperature is below 5°C

Technical Information

No	ITEM	STANDARD	①	②	③	CONCLUSION
1	<u>Water impermeability pressure Map</u> ≥	0.3	0.3	0.3	0.3	PASS
2	<u>Thickness MM</u>	1.5±0.01	1.50	1.51	1.50	PASS
3	<u>Softening point</u>	110°C	110°C	110°C	110°C	PASS
4	<u>Operating Temperature short periods</u>	-20°C+90°C	-20°C 90°C	-20°C 90°C	-20.5°C 90°C	PASS
5	<u>Elongation %</u> ≥	300	306	310	305	PASS
6	<u>Tear Resistance N/50mm</u> ≥	200	210	212	208	PASS
7	<u>Peel Adhesion N/M</u>	1576	2018	2182	2009	PASS
8	<u>Flexibility</u>	-30°C	-30°C	-30°C	-30°C	PASS
INSPECTION BASIS		*ASTM D 1000 ** ASTM D 1004*				

Packing size

- Roll 10 cm X 1m
- Roll 10 cm X 3m
- Roll 20 cm X 3m
- Roll 30 cm X 3m
- Roll 30 cm X 10m
- Roll 30 cm X 10m (Black Foil)
- etc

DR. FIXIT GAP SEAL TAPE

Self Adhesive Bituminous Strip with Aluminums Foil Finish

Shelf Life & Storage

- Shelf life is 24 months from the date of manufacturing.
- Stored in cool and dry place

Health & Safety Precaution

- As with all bitumen products caution should always be exercised. Protective clothing such as gloves and goggles should be worn. Treat any splashes to the skin or eyes with fresh water immediately. Should any of the products be accidentally swallowed, do not induce vomiting, but call for medical assistance immediately.

Disclaimer

The product information and the recommendations relating to the application and end-use of Dr.Fixit products, are based on Dr.Fixit's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Dr.Fixit's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Dr.Fixit reserves the right to change the properties of its products without notice, so the company does not assume liability of any legal from this product information.



Pidilite Bamco Limited (A group company of Pidilite Industries Ltd.)
699 Modernform Tower 15,17 FL., Srinakarin Rd., Pattanakarn, Suan Luang, Bangkok 10250, THAILAND.
T. +662 722-8535 F. +662 722-8381
Website: www.dr-fixit.co.th
E-mail: sales@pidilitebamco.com
Helpline Call +662 722 8535 #101