

Dr. Fixit SLC Primer

Description

Dr. Fixit SLC Primer is primer agent use as a self-leveling mortar. It is use on smooth and porous concrete surface. Improve bonding between old and new concrete surface and reduces formation of air bubble in concrete substrates.

Dr. Fixit SLC Primer is primer agent use as a self-leveling mortar. It is compromise of high grade synthetic rubber and various additives.

Area of Application

- Old and new concrete.
- Self-leveling mortar.

Rate of Uses

* **Theoretical consumption without allowance for loss.**

Rate of Uses					
	Litre / m ²			m ² / gallon (5 Litre)	m ² / gallon (20 Litre)
	Standard	At Least	At Most		
1 Coat	0.17	0.15	0.20	29	117

Method of Application

1. Substrate preparation:

- The substrate must be clean and dust free.
- Remove any impurities and loose materials.
- New concrete surface must be at least 28 days old.

2. Application:

- Paint on surface of ratio 0.15-0.2 Liter/m².
- Leave it to dry for 15-20 minutes (depending on weather).
- Can immediately adjust surface after drying cycle.
- SLC Primer pot life is 24 hours.

3. Cleaning:

- Clean the equipment with water immediately after finish working.

Precaution and limitations

- Avoid working while temperatures below 5 ° C and the weather are extremely hot or rainy.

Technical Information

Properties	Standard / Testing Method	Result test
Appearance	W-TP-021	White liquid
Viscosity (KU)	W-TP-001	40-47
Density	W-TP-009	1.00-1.05 g/ml.
pH	W-TP-022	9.5-10.5
Dry content	W-TP-010	19-21%

Dr. Fixit SLC Primer

Packing;

- Gallon 5 Liter, Gallon 20 Liter

Storage;

- 12 month in sealed container under shade and dry area.

Precaution and limitations;

- Wear gloves and safety glass when applying application.

Disclaimer

The product information and the recommendations relating to the application and end-use of Dr.Fixit products, are based on Dr.Fixit's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Dr.Fixit's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Dr.Fixit reserves the right to change the properties of its products without notice, so the company does not assume liability of any legal from this product information.

	Pidilite Bamco Limited (A group company of Pidilite Industries Ltd.) 699 Modernform Tower 15,17 FL., Srinakarin Rd., Pattanakarn, Suan Luang, Bangkok 10250, THAILAND. T. +662 722-8535 F. +662 722-8381 Website: www.dr-fixit.co.th E-mail: sales@pidilitebamco.com Helpline Call +662 722 8535 #101
---	--