

Dr. Fixit Hi-gloss 4

Bituminous paint and corrosion protection coating

Description:

Dr. Fixit High Gloss 4 is a color black varnish anti-rust coating and corrosion. It can be well bonded to the surface of various materials. When dry, it has a beautiful shiny black color, no smell, can be flexible. It was not contaminated hands, easy to use; prevent water and steam, coughing, salt water, acid and alkali.

Dr. Fixit High Gloss 4 is made from special bitumen or asphalt mixed with hydrocarbon solutions and additives. Manufactured according to British standards (BS 3416)

Area of Application:

- Used to paint or spray on metal, concrete, wood, brick and lightweight insulation.

Rate of Uses

Rate of Uses						
	Liter / m ²			m ² /gallon (3.5 Liter)	m ² / Pails (18 Liter)	m ² / Drum (200 Liter)
	Standard	At Least	At Most			
1 Coat	0.15	0.10	0.20	23	120	1333
2 Coats	0.30	0.20	0.40	11	60	666
Total 2 Coats	0.30	0.20	0.40	11	60	666

Method of Application

1. Surface Preparation

- Surface must be dry clean and free from dust, dirt, grease, moss or any other foreign matter.

2. Application

- Apply by brush or spray to the area to be coated. Dilution can be made by using kerosene.
- Allow to dry for 2-3 hours before apply second coat for long service life.

3. Cleaning

- Clean with kerosene or white spirit.

Dr. Fixit Hi-gloss 4

Bituminous paint and corrosion protection coating

Technical Information

Properties	Standard/Test Method	Results Test
1.Viscosity, cPs	Brookfield	650-850
2.Density, g/ml	ASTM D-70	0.94
3.Drying time, hrs	4 max	2-3
4.Flash point, °C	ASTM D3278-20	47 °C
5.Non Volatile Matter % w/w min	ASTM D-95	60 ±1

Packing

- 3.5 Liter/Gallon
- 18 Liter/Pail
- 200 Liter/Drum

Storage

- Always store in closed container and kept under shed.
- Keep away from sources of ignition, normal precautions against fire must be taken

Health & Safety Precautions

- The solution contains flammable solvents. Keep away from naked flames, sources of ignition etc.
- No smoking while applying.
- Use the primer in good ventilated area.
- In case of fire, use carbon dioxide, dry chemical, foam fire extinguisher or sand. Do not use water.
- In case of eyes contact, irrigate the eyes with clean water and seek medical attention.
- For skin contact, remove skin contamination with hand cleaner, wash with soap and water.
- Seal the container tightly after use.

Disclaimer

The product information and the recommendations relating to the application and end-use of Dr.Fixit products, are based on Dr.Fixit's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Dr.Fixit's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Dr.Fixit reserves the right to change the properties of its products without notice, so the company does not assume liability of any legal from this product information.



Pidilite Bamco Limited (A group company of Pidilite Industries Ltd.)
699 Modernform Tower 15,17 FL.,Srinakarin Rd.,Pattanakarn, Suan Luang, Bangkok 10250, THAILAND.
T. +662 722-8535 F. +662 722-8381
Website: www.dr-fixit.co.th
E-mail: sales@pidilitebamco.com
Helpline Call +662 722 8535 #101